

NOV 17 2006

PAGE 5/23 * RCVD AT 11/17/2006 8:46:55 PM [Eastern Standard Time] * SVR:USPTO-EFAXF-6/37 * DNIS:2738300 * CSID: * DURATION (mm-ss):07-48

CLAIMS

Claim 1. (Currently amended). An improved vapor generator and control system comprises comprising:

- (1) a vaporization chamber for generating superheated vapor substantially instantaneously from liquid upon its entry therein; and
- (2) at least one input port for input therethrough of liquid for vaporization in said vaporization chamber, said input port including means connectable to adjustable control means for adjustably controlling ongoing input of liquid during ongoing input of said liquid into said vaporization chamber whereby generation of superheated vapor is adjustably controllable while said system is in operation.

Claim 2. (Currently amended). The invention as set forth in Claim 1 wherein said adjustable control means adjustably controls volume of liquid input into said vaporization chamber and thereby adjustably controls volume of output of superheated vapor from said vaporization chamber.

Claim 3. (Original). The invention as set forth in Claim 1 further including at least one output port for output therethrough of superheated vapor from said vaporization chamber, said at least one output port including means connectable to output control means for controlling output from said vaporization chamber.

Claim 4. (Currently amended). The invention as set forth in Claim 3 1 wherein said adjustable [output] control means for adjustably controlling input of liquid into said vaporization chamber adjustably controls pressure of liquid input into said vaporization chamber and thereby adjustably controls pressure of output from said vaporization chamber.

Claim 5. (Original). The invention as set forth in Claim 3 wherein said output control means controls volume of output from said vaporization chamber.

Claim 6. (Original). The invention as set forth in Claim 3 wherein said output control means comprises at least one valve member.

Claim 7. (Original). The invention as set forth in Claim 3 wherein said output control means includes means for directing in a selected direction superheated vapor from said vaporization chamber.

Claim 8. (Original). The invention as set forth in Claim 7 wherein said output control means comprises at least one valve member.

Claim 9. (Original). The invention as set forth in Claim 7 wherein said output control means is adjustable for directing superheated vapor from said vaporizing chamber in a plurality of selected directions.

Claim 10. (Original). The invention as set forth in Claim 8 wherein said at least one valve member comprises a plurality of valve members at least two of which are adjustable to direct output superheated vapor in substantially perpendicular directions.

Claim 11. (Original). The invention as set forth in Claim 3 wherein said output port is connectable to at least one object to which superheated vapor is to be directed.

Claim 12. (Original). The invention as set forth in Claim 3 wherein said output control means is connectable to at least one object to which superheated vapor is to be directed.

Claim 13. (Original). The invention as set forth in Claim 1 wherein said vaporization chamber has at least a portion of an inner surface which is rough.

Claim 14. (Original). The invention as set forth in Claim 1 wherein said vaporization chamber has at least a portion of an inner surface which defines at least one groove.

Claim 15. (Original). The invention as set forth in Claim 14 further including at least one groove other than the first-mentioned groove and wherein said first-mentioned groove and said second-mentioned groove intersect.

Claim 16. (Original). The invention as set forth in Claim 1 wherein said vaporization chamber has at least a portion of an inner surface which defines a plurality of grooves.

Claim 17. (Original). The invention as set forth in Claim 16 wherein said plurality of grooves vary substantially randomly in depth in a range substantially .030 inch to .050 inch.

Claim 18. (Original). The invention as set forth in Claim 4 wherein said output control means is configured to be hand-held by an operator and to be controlled by said operator.

Claim 19. (Original). The invention as set forth in Claim 1 wherein said vaporization chamber has at least a portion of an inner surface which includes at least one perforation.

Claim 20. (Original). The invention as set forth in Claim 1 wherein said vaporization chamber has at least a portion of an inner surface which includes at least one irregularity.

Claim 21. (Currently amended). A method of fabricating a superheated vapor generator and control system comprising the steps of:

- (a) providing at least two separate parts of a vapor generator;
- (b) fastening said parts together to form a superheated vapor generator defining a vaporization chamber, said superheated vapor generator having capability for substantially instantaneous vaporization of liquid upon entry thereof into said vaporization chamber; and
- (c) providing means for connecting to adjustable control means for input to said vapor generator for adjustably controlling ongoing input of liquid into said vaporization chamber during said ongoing input of liquid, thereby providing the capability of adjustably controlling output

RECEIVED
CENTRAL FAX CENTER

NOV 17 2006

of superheated vapor from said vaporization chamber without requiring
said system to cease operation.

Claim 22. (Original). The method as set forth in Claim 21 further including the step of providing control means at the output of said vapor generator.

Claim 23. (Original). The method as set forth in Claim 21 further including the step of defining at least one groove in at least a portion of an inner surface of at least one of said ports.

Claim 24. (Original). The invention as set forth in Claim 21 further including the step of defining a plurality of grooves in at least a portion of an inner surface of at least one of said ports, such that said grooves vary in depth substantially randomly in height and depth in the range of .030 inch to .050 inch.

Claim 25. (Original). The invention as set forth in Claim 22 wherein said output control means are adjustable to control the direction of superheated vapor from said vaporization chamber.

Claim 26. (Currently amended). A method for cleaning selected objects comprising the steps of:

- (a) generating superheated vapor by substantially instantaneously vaporizing liquid into superheated vapor through subjecting said liquid to superheating; and
- (b) providing capability of adjustably controlling volume, pressure or direction velocity on line of output superheated vapor for a selected object to be cleaned by adjustably controlling in an ongoing manner volume, pressure or velocity of said liquid upon being subjected to said superheating.

Claim 27. (Currently amended). A method for propulsion comprising the steps of:

- (a) generating superheated vapor by substantially instantaneously vaporizing liquid into superheated vapor through subjecting said liquid to superheating; and
- (b) providing the capability of controlling output of superheated vapor substantially continuously to provide propulsion, by adjustably controlling volume, pressure or velocity of said liquid upon being subjected to said superheating.